FORSAGE
Lubricants

Forsage-Oil LLC
1, Neftebaza Street, Koptsevy Hutora village
Lipetsk, 398501, Russia
ITN 4813026820 IEC 481301001
tel./fax: +7 4742 35-35-66
info@forsage-lube.com www.forsage-lube.com

FORSAGE Lubri Force Litol 24
Multipurpose Grease

DESCRIPTION

FORSAGE Lubri Force Litol 24 - multipurpose lithium grease with antioxidant and viscosity index additives.
FORSAGE Lubri Force Litol 24 - designed for use in rolling and sliding bearings of all types, hinges, gears and other gear, the friction surfaces of the knee and tracked vehicles, industrial machinery, electrical machinery, and so on.

Is used for medium and high loads and temperatures from -40 to +120 °C.

FEATURES

FORSAGE Lubri Force Litol 24 has the following advantages:

- High colloid, chemical and mechanical stability
- High-quality product in economy class
- Can be used for conservation of parts

TYPICAL CHARACTERISTICS

FORSAGE Lubri Force	**Litol 24**
NLGI	3
Dropping point, °C	185
Penetration at 25 oC, with mixing, 0.1 mm, within a range of	220-250
Colloidal stability, %, max	12
Corrosion attack on metals	prevents
Four-ball machine: Welding load, N Critical load, N Wear Index, N	 1410 630 28

Produced according to GOST 21150-87
This information serves as reference and can be changed without notice.

FORSAGE
Lubricants

Forsage-Oil LLC
1, Neftebaza Street, Koptsevy Hutora village
Lipetsk, 398501, Russia
ITN 4813026820 IEC 481301001
tel./fax: +7 4742 35-35-66
info@forsage-lube.com www.forsage-lube.com

FORSAGE Lubri Force Litol 24
Смазка общего назначения

ОПИСАНИЕ

FORSAGE Lubri Force Litol 24 - многоцелевая литиевая смазки с антиокислительной и вязкостной присадками .
Смазка FORSAGE Lubri Force Litol 24 – применяется в подшипниках качения и скольжения всех типов, шарнирах, зубчатых и других передач, в поверхностях трения коленых и гусеничных транспортных средств, индустриальных механизмах, электрических машинах и т. п..

Используются при средних и высоких нагрузках и в диапазоне температур от -40 до +120 °С.

ПРЕИМУЩЕСТВА

FORSAGE Lubri Force Litol 24 обладает следующими преимуществами:

- Высокая коллоидная, химическая и механическая стабильность
- Высококачественный продукт в эконом-классе
- Может использоваться для консервации деталей

ТИПИЧНЫЕ ХАРАКТЕРИСТИКИ

FORSAGE Lubri Force	**Litol 24**
Класс вязкости по NLGI	3
Температура каплепадения, °С	185
Пенетрация при 25 °С с перемешиваем, 0,1 мм, в диапазонах	220-250
Коллоидная стабильность, %, не более	12
Коррозийное воздействие на металл	выдерживает
характеристики на четырехшариковой машине при температуре (20 ± 5) °С: -нагрузка сваривания (РС8), Н, не менее -критическая нагрузка (Рк), Н, не менее -индекс задира (И3), Н, не менее	 1410 630 28

Изготавливается по ГОСТ 21150-87
Данная информация является справочной и может быть изменена без уведомления.