

FORSAGE Outboard 2T Mineral Engine Oil 2T Stroke

DESCRIPTION

FORSAGE Outboard 2T - mineral all-season motor oil for 2-cycle outboard engines. The selected base stocks and additives provide an excellent strong oil film for ultimate protection and lubrication under a wide range of temperatures. This oil gives excellent lubrication and helps prevent deposits from forming in the combustion chamber. Standard injection 1:50.

FEATURES

FORSAGE Outboard 2T has the following features:

- Smooth and fast cold start
- Good wear protection resists high speed revving
- Motor protection against rust and corrosion, extends the life of engine parts
- With a pour point of -35 °C has no problems with fishing trips in the wintertime

STANDARDS/APPROVALS

FORSAGE Outboard 2T comply with **API TC** grade.

TYPICAL CHARACTERISTICS

FORSAGE Outboard 2T	
Kinematic viscosity at 100 °C, mm ² /s	8.5
Viscosity index	140
Density at 20°C, g/cm ³	0.870
Flash point, °C	95
Pour point, °C	-37
TBN, mg KOH/g	10.0

Produced by TU.
This information is a reference and can be changed without notice.



FORSAGE Outboard 2T **Минеральное масло для двухтактных двигателей**

ОПИСАНИЕ

FORSAGE Outboard 2T - моторное масло для 2-тактных подвесных моторов.

Высокоэффективное моторное масло для любых 2-тактных подвесных двигателей с воздушным и водяным охлаждением. Это масло обеспечивает отличную смазку и помогает предотвратить образование отложений в камере сгорания.

Используется в качестве компонента в масляно-топливной смеси в стандартном соотношении 1:50, однако следует придерживаться рекомендаций производителей двигателей.

ПРЕИМУЩЕСТВА

FORSAGE Outboard 2T обладает следующими преимуществами:

- Плавный и быстрый холодный старт
- Хорошая защита от износа, выдерживает работу на высоких оборотах
- Защита двигателя от ржавчины и коррозии, продлевая срок службы различных деталей двигателя
- Температура застывания -35°C . Масло прекрасно работает на рыбалке в зимний период

СТАНДАРТЫ/СЕРТИФИКАТЫ

FORSAGE Outboard 2T соответствует требованиям **API TC**.

ТИПИЧНЫЕ ХАРАКТЕРИСТИКИ

FORSAGE Outboard 2T	
Кинематическая вязкость при 100°C , $\text{мм}^2/\text{с}$	8.5
Индекс вязкости	140
Плотность при 20°C , $\text{гр}/\text{см}^3$	0.870
Температура возгорания, $^{\circ}\text{C}$	95
Температура застывания, $^{\circ}\text{C}$	-37
Щелочное число, $\text{мгКОН}/\text{гр}$	10.0

Изготавливается по ТУ.

Данная информация является справочной и может быть изменена без уведомления.

